

Drums

Drums Boxes



In order to help you in your drums management, Wilitec drums are fully compatible with the NOV ASEP drums series 06 BC and SC; means ASEP drums can be used on Wilitec units and Wilitec drums on NOV ASEP units.

The drum box is a single piece design, steel frame construction, and can accommodate all types of Wilitec drums. Forklift pockets and lifting padeyes are integrated into frame structure.

Full compatibility with the NOV Elmar units (ex- ASEP).



Model W06W-F24C14 (slickline) Dimensions & Weights (excluding wire)

drum	mm Flange	600
	mm Core	350
	mm Width	700
weight	kg	360
	lbs	794



Model W06W-F24C10 (braidedline) Dimensions & Weights (excluding wire)

drum	mm Flange	700
	mm Core	260
	mm Width	700
weight	kg	338
	lbs	745

Drum Capacity		0.108"	0.125"	3/16"	7/32"	1/4"
W06W-F24C14 (SC06)	m	19600	14660	6470	-	-
	ft	64400	48100	21240	-	-
W06W-F24C14 (BC06)	m	-	-	11550	8350	6330
	ft	-	-	37900	27400	20780



Model DB-W700-02
Dimensions & Weights (excluding drum & wire)
Lifting Padeyes certified as per EN 12079

box (L x W x H)	m	1.30 x 0.93 x 0.85	ft	4.26 x 3.06 x 2.79
weight :	Max Gross	kg 2500	lbs	5512
	Tare Mass	kg 350	lbs	772
	Pay Load	kg 2150	lbs	4740



Model DB-W700-01
Dimensions & Weights (excluding drum & wire)
Full Structural certification DNV 2.7-1 / EN12079

box (L x W x H)	m	1.31 x 0.93 x 1.00	ft	4.26 x 3.06 x 3.28
weight :	Max Gross	kg 2500	lbs	5512
	Tare Mass	kg 350	lbs	772
	Pay Load	kg 2150	lbs	4740

Drum Weight with Cable		Drum Empty	0.108"		0.125"		3/16"		7/32"		1/4"	
			ft	20000	25000	20000	25000	20000	25000	25000	25000	
W06W-F24C14 (SC06)	kg	360	300	375	390.4	488	774	-	-	-	-	-
	lbs	794	661	827	861	1076	1707	-	-	-	-	-
W06W-F24C14 (BC06)	kg	338	-	-	-	-	-	968	1265	1676	-	-
	lbs	745	-	-	-	-	-	2134	2789	3695	-	-

certificate by



contact us : info@wilitec.com | visit us : www.wilitec.com

