

The Compressor has been designed for wireline operations where an independent air supply is required. The frame incorporates forklift pockets and lifting padeyes for crane handling.

A wide range of compressor Zone 2 and certified DNV 2.7-1 / EN12079, air delivery and output pressure, can be manufactured.

A wide range of stand-alone compressors for hazardous area zone2.

Model Atlas Copco 190cfm/7bars Zone2

- Diesel Deutz 3 cylinder engine D2011L03 zone2 oil cooled, 36kw
- Spring starting system
- Diesel Engine Protection EN1834-1 ATEX94/9/EC
- Water cooled exhaust manifold and heat exchanger for T3=200deg
- Inlet flame trap for IIB operation
- Inlet shut down valve and fuel shut down
- Exhaust flametrap
- Crankcase ventilation flametrap
- Antistatic fan belts
- Spark arrestor
- High water coolant temperature shut down at 100deg C
- High exhaust gas temperature shut down at 200deg C-T3
- Low oil pressure shut down at 0.8bar
- Overspeed valve shut down
- Screw fitting oil dipstick/ filter cap

- Compressor Atlas Copco XAHS97, 190cfm 7bars zone2
- Clearly laid out irgonomic anodized aluminium control panel with engine speed/ oil pressure/ oil temperature/ coolant temperature/ exhaust temperature/ air pressure gauges and hour meter
- Protection for all drive belts
- Sound proof cabinet
- Skid mounted frame structure certified DNV2.7-1/ EN12079

Dimensions & Weight

Dimension (L x W x H)	m	2.50 x 1.50 x 1.65	ft	8.20 x 4.92 x 5.41
Weight	ka	2700	lbs	5952









certificate by







