

The Generator has been designed for wireline operations where an independent power supply is required. The frame incorporates forklift pockets and lifting padeyes for crane handling.

A wide range of generator Zone2 and certified DNVGL 2.7-1 / EN10855, from portable 10kva up to 400kva can be manufactured.

A wide range of stand-alone power generators for hazardous area zone2.

Diesel Genset 15kVA Zone2 3 Phases 415V

- Diesel engine ATEX water cooled Perkins 404D-22G or equivalent 20.3kW @ 1500rpm (50hz) / 23.9kW @ 1800rpm (60Hz)
- Spring starting system (air & electrical starter optional)
- Diesel Engine Protection EN1834-1 ATEX94/9/EC
- Water cooled exhaust manifold and heat exchanger for T3=200deg
- Inlet flame trap for IIB operation
- Inlet shut down valve and fuel shut down
- Exhaust flametrap
- Crankcase ventilation flametrap
- Antistatic fan belts
- Spark arrestor
- High water coolant temperature shut down at 100deg C
- High exhaust gas temperature shut down at 200deg C-T3
- Low oil pressure shut down at 0.8bar
- Overspeed valve shut down
- Screw fitting oil dipstick/ filter cap

- Brushless alternator twin bearing MIRETTI (original Mecc Alte ECP32-2M/4B)
- Connectors 415VAC 3Ph and 240VAC 1Ph
- Connection 24VDC optional
- Totally enclosed TEFC air cooled IP55 non sparking
- Voltage Regulation AVR
- ExnA/BIIT3, Atex 3G
- Class H insulation continuously rated and twin bearing
- Control box ATEX Zone2 (brand WAROM)
- MCCB/ ELCB 30mA
- Clearly laid out irgonomic anodized aluminium control panel with engine speed/ oil pressure/ oil temperature/ coolant temperature/ exhaust temperature/ air pressure gauges and hour meter
- Protection for all drive belts
- Skid mounted frame structure certified DNVGL2.7-1/EN10855
- Fuel tank 100 liters Aluminium
- Protection doors Aluminium

Dimensions & Weight

Dimension (L x W x H) m 1.90 x 1.05 x 1.56 ft 6.23 x 3.44 x 5.12 Weight (standard version) kg 1800 lbs 3968





certificate by









